

# TECHNICAL DATA SHEET

**SANDER XXT ESD S3 No. 769731**


**Sz. 35 - 49**



## LABELLING ACCORDING TO STANDARD

|   |   |
|---|---|
| Standard for safety footwear<br>EN ISO 20345 S3 | Basic requirement for S3:<br><b>A</b> Antistatic shoe - <b>E</b> Energy absorption in the heel - <b>FO</b> Fuel resistance - <b>WRU</b> Water penetration and water absorption resistant upper - <b>P</b> Penetration resistance - Closed heel area - Profiled outsole            |
| Additional requirements                         | <b>SRC</b> Slip resistance: Slip resistant on floors of ceramic tiles with a sodium lauryl sulfate (SLS) solution and on steel floors with glycerol. When it comes to slip resistance as defined by EN ISO 20345, SRC signifies the best possible rating a safety shoe can reach. |








## FORM

|  |   |
|--|---|
| Safety laced boot<br> | Form B - in size 42, the upper height must be at least 11.3 cm. |
|--|---|

## AREAS OF APPLICATION

|                      |  |
|----------------------|--|
| Areas of application | <p>Indoors and outdoors</p> <p>Areas where exposure to moisture is expected (S2)</p> <p>Areas where there is a risk of penetration from pointed and sharp objects (S3)</p> <p>Areas where there is a risk of electrostatic discharge (ESDS/ESD)</p> <p>E.g. airports, airplane construction, automobile manufacturing</p> <p>No scratches from metal parts</p> <p>Close to induction loops / metal detectors</p> <p>Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step.</p> <p>Workplaces on hard Undergrounds: The revolutionary Infinergy® sole core cushions impacts and provides for a rebound effect when the compressive impulse subsides - for more energy in every step.</p> |
|----------------------|--|

## FEATURES

|   |  |   |
|---|--|---|
| ESD equipment   | Thanks to its excellent discharge capability, the shoe is suitable for work in ESD sensitive or electrostatically protected areas (EPA). The shoes comply to the standard 61340-5-1.   |    |
| Sizes (unisex model)  | <ul style="list-style-type: none"> <li>Expanded size range: available in sizes 35 - 49</li> </ul>  |   |
| Certification in accordance with DGUV rule 112-191  | <ul style="list-style-type: none"> <li>Certified for orthopaedic inserts</li> </ul>  |    |
| Low weight  | <ul style="list-style-type: none"> <li>Use of especially light textile materials</li> <li>Comfortable</li> </ul>   |   |
| Full, padded bellows tongue   | <ul style="list-style-type: none"> <li>Excellent wearing comfort: The tongue prevents pressure marks and avoids dirt from entering into the shoe.</li> </ul>   |   |
| Collar padding  | <ul style="list-style-type: none"> <li>Excellent wearing comfort: the ankle-wrapping, softly padded upper edge provides for stability and grip in the shoe.</li> </ul>   |   |
| Reflective material   | <ul style="list-style-type: none"> <li>Good visibility in the dark</li> </ul>  |    |
| Sole core made of Infinergy® by BASF<br> | The sole core consists of expanded, thermoplastic polyurethane in the form of oval foam beads. These stick together and are very light and elastic. This revolutionary technology cushions the impact and bounces back extremely well on pressure, so that the energy can be returned to the wearer. Even under low temperatures of -20 °C, the core maintains its high elasticity.  |    |
| No metal or leather   | <ul style="list-style-type: none"> <li>Low weight</li> <li>Suitable for work areas sensitive to metal</li> <li>Does not trigger metal detectors</li> <li>Use around induction loops is possible</li> <li>Suitable for persons allergic to leather</li> </ul>   |   |
| Ergonomic Product IGR certification   | The IGR quality seal (Interessengemeinschaft der Rückenschullehrer/-innen e.V. / Association of back specialists) confirms the highly praised features and practical functionality of the tested products. The IGR certification attests the degree of the product's customisability to the physical characteristics of the test person. In accordance with DIN 33419 / EN ISO 15537, the product's usability and ergonomics were tested. Products recommended by IGR e.V. bear the title "Ergonomic Product". |  |
| Winner Plus X Award   | The independent jury for the Plus X Award, the Innovation Prize for Technology, Spot, and Lifestyle, grants a total of seven seals of approval to brands that offer products with a competitive edge in terms of quality and innovation. ELTEN has always seen itself as an innovative business at the cutting edge of technology.   |  |


## UPPER MATERIAL

|   |   |
|---|---|
| Hydrophobized microfibre                                    | <ul style="list-style-type: none"><li>• Areas of application S2/S3</li><li>• Synthetic material</li><li>• Particularly soft</li><li>• Retains its shape</li><li>• Tear-resistant</li><li>• Dries quickly</li><li>• Abrasion-resistant and light</li><li>• Water penetration and absorption in accordance with EN ISO 20345 S2; an improved resistance against water penetration is achieved by a special hydrophobation of the material</li></ul>                       |
| Textile material Cordura® (hydrophobized)<br><b>CORDURA</b> | <ul style="list-style-type: none"><li>• Areas of application S2/S3</li><li>• Synthetic material</li><li>• Particularly resistant to wear and tear</li><li>• Retains its shape</li><li>• Tear-resistant</li><li>• Dries quickly</li><li>• Abrasion-resistant and light</li><li>• Water penetration and absorption in accordance with EN ISO 20345 S2; an improved resistance against water penetration is achieved by a special hydrophobation of the material</li></ul> |

## LINING


|                          |  |
|--------------------------|--|
| Breathable fabric lining | <ul style="list-style-type: none"><li>• Climate-regulating</li><li>• Good ventilation</li><li>• Skin-friendly</li><li>• High absorption and emission of moisture</li></ul> |
| Heel pocket lining       | <ul style="list-style-type: none"><li>• The abrasion-resistant microfibre material is particularly sturdy and provides for a pleasant wearing comfort.</li></ul>           |

## TOE PROTECTION CAP

|  |   |
|--|---|
| Composite toe cap<br> | <ul style="list-style-type: none"><li>• Protection against impacts of min. 200 joules and pressure loading of min. 15 kN</li><li>• Permanent edge coverage for cushioning</li><li>• Ergonomically shaped</li><li>• Comfortable toe room</li><li>• Good coverage of the little toe area</li><li>• Low weight - weighs less than conventional steel caps</li><li>• 100% metal-free</li><li>• 100% anti-magnetic</li></ul> |
|--|---|

## INLAY SOLE

Full-length inlay sole  
ESD PRO



- ESD EQUIPMENT: Protection against electrostatic discharge (ESD). The full-length, exchangeable inlay sole is conductive and designed for the use in ESD safety footwear according to the standards DIN EN ISO 20345 and DIN EN 61340-5-1.
- The full-length, exchangeable inlay sole provides the highest possible comfort in safety shoes.
- The inlay sole is functionally absorbing and releasing moisture and thus provides for a pleasant foot climate.
- The extreme softness of the PU foam absorbs shocks on impact and increases walking comfort.
- Improvement of the shoe climate thanks to the PU foam's open cell structure. So the foot is always kept comfortably dry.

## PENETRATION RESISTANCE

Metal-free penetration  
protection

The textile midsole complies with the penetration safety standard EN 12568 and furthermore fulfils the additional requirements for penetration protection in accordance with EN ISO 20344 / 20345. The light and flexible material enables an increased elasticity of the shoe, which can particularly be recognized when working on uneven grounds or on your knees.

The textile variant offers 100 % foot coverage compared to steel midsoles (foot coverage 85 % due to limits in the shoe manufacturing process). Being 100 % metal-free and antimagnetic, this equipment is used as penetration protection in safety shoes.

## OUTSOLE

WELLMAXX TRAINERS  
double-density sole with  
profile



- Excellent slip resistance
- Antistatic

Outsole: PU (polyurethane)

- Colour: lightgrey
- Profile depth: 4.0 mm
- Abrasion-resistant
- Heat-resistant to approx. 130°C
- Flexible at cold temperatures to approx. -20°C
- Oil and fuel resistant

Midsole: PU (polyurethane) with a core made of Infinergy® by BASF

- The soft PU core provides a good impact absorption and high wearing comfort
- The core made of Infinergy® provides a very good cushioning with rebound effect