

# TECHNICAL SPECIFICATION



## Single Tool Lanyard

Single Tool Lanyard / FAR0502



### DESCRIPTION

Convenient stretch lanyard for tool holding, made from highly visible 16mm tubular webbing. Max 10kg.

### OPTIONS

#### Single Tool Lanyard (FAR0502)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 12 May 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Length  
0.85m to 1.35m



Rated Weight / Load  
10kg (Tools)

Material  
Highly Visable 16mm Tubular Elasticated Webbing

Delivered With  
Lightweight Connector For Attachment To The  
User's Belt

## DOWNLOADS

 [Image Pack \(ZIP\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 12 May 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

